

# RRSP01

# LUMIDENSE

Professional Lighting Solutions Partner

## RECESSED LED SLIM PANEL LIGHT

### TECHNICAL SPECIFICATION

**Housing:** Die cast aluminum trim, Presses steel back cover.

**Protection:** IP20.

**Light Shade:** Opal PS diffuser.

**Rendering Index:** CRI > 80


**Available CCT:** 3000K, 4000, 6500K.

**Light Source:** CREE, BRIDGELUX.

**Lifetime:** 30,000 Hrs 25C. 3Y warranty CB Comply.





### PHOTOMETRIC DATA



### ORDERING INFORMATION

FAMILY SIZE	MAX WATTAGE	OUTPUT LUMEN	OUTER SIZE(A,H)	CUT OUT (C)
RRSP01-6	6W	360LM	120MM, 12MM	105MM
RRSP01-9	9W	700LM	150MM, 12MM	135MM
RRSP01-12	12W	900LM	170MM, 12MM	155MM
RRSP01-15	15W	1100LM	190MM, 12MM	175MM
RRSP01-18	18W	1400LM	225MM, 12MM	210MM
RRSP01-24	24W	1900LM	300MM, 12MM	285MM

### Dimensions



### Surface Ring Design

Surface Ring

+

Slim Panel

↓

Surface Panel



### ZHONGSHAN LUMIDENSE TRADING CO LTD.

Room 2008, Yihualingfeng Building,  
No.38 Yuelai south Road, Shiqi district,  
Zhongshan city, china.  
P.O.:528400

Phone: +86 760-88238830  
Mobile: +86 131 2934 5064  
Website: www.lumidense.com  
Email: lumidense@lumidense.com